32Ch CIF/D1

SA-32800(4CH D1 + 28CH CIF)

Front Panel

Rear Panel

Specifications

MODEL		SA-32800
System	Compression Format	Baseline H.264
	OS	Embedded Linux
Video	Input	32CH Standard BNC
	Standard Output	VGA, CVBS
	Advanced Output	HDMI, Spot
Audio	Input	16CH
	Output	1CH
	Two way audio	Yes
Recording	Real-Time Recording	4CH D1 + 28CH CIF Real-Time
	HD-SDI	No
	960H	No
	D1	310FPS(NTSC)/260FPS(PAL)
	CIF	960FPS (NTSC)/800FPS (PAL)
	Recording Mode	Schedule, Manual, Motion, Sensor
Playback	Playback Channel	16CH
	Search Mode	Time, Event, File Management
Backup	USB	1 USB 2.0 Port
	DVD Burner	Optional
	Backup Format	AVI/DAT
Remote Application	Dual Stream	Master Stream 1-25/30FPS@CIF, Sub-Stream 1-6/7FPS@CIF
	Browser	IE, Chrome, Safari, Firefox (Mac OS, Windows XP/Vista/7/8)
	Master Stream in Network	Yes
	CMS	Yes
	3G	ProvisionCAM for iPad/iPhone/Blackberry/Android/Symbian/Windows Mobile
	User Access	10 Users Online with Professional Autorithy Management
Alarm	Input	16
	Output	4
Storage	HDD	8 SATA (2TB)
	E-SATA	1 E-SATA
PTZ	Connection	2xRS-485
	Supported Protocol	Pelco D, Pelco P, Samsung, Visca
	Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
Network	Ethernet	1000 Mbps (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP
Others	Dimension	W550XD535XH155
	IR Controller	Yes
	Power Supply	100-240 VAC
	Operating Temperature	0°C ~50°C