

# 32 CH AHD DVR

## SA-32400AHD-2 (2U)

720P 1080P



MODEL		SA-32400AHD-2 (2U) - Half Real-Time Mode	SA-32400AHD-2 (2U) - Real-Time Mode	
System	Compression Format	High profile H.264		
	ONVIF	No		
	Format	AHD / CVBS		
Video	Input	32CH AHD Standard BNC		
	Standard Output	HDMI, VGA (800x600, 1024x768, 1280x1024)		
Audio	Input	16CH		
	Output	1CH		
	Two Way Audio	Yes		
Recording	AHD	Recording	32CH 1080P Half Real-Time	16CH 1080P Real-Time
		2MP (1080P)	480FPS (NTSC)/400FPS (PAL). Up to 15/12FPS	
		1MP (720P)	960FPS (NTSC)/800FPS (PAL)	
	Analog	Recording	32CH 960H Real-Time	16CH 960H Real-Time
		960H	480FPS (NTSC)/400FPS (PAL)	
		D1	No	
	IP	CIF	No	
		Recording	No	
		3MP	No	
		2MP (1080P)	No	
		1.3MP (960P)	No	
	General	1MP (720P)	No	
Recording Modes		Schedule, Manual, Motion, Sensor		
Playback	AHD/CVBS Playback	8CH	4CH	
	IP Playback	No		
	Search Mode	Time, Event, File Management		
Backup	USB	2 USB 2.0 Port		
	DVD Burner	Optional		
	Backup Format	AVI/DAT		
Remote Application	AHD Stream	Master & Sub-Stream: Up to 1-12/15FPS@1080P	Master & Sub-Stream: Up to 1-25/30FPS@1080P	
	Analog Stream	Master & Sub-Stream 1-25/30FPS@960H		
	IP Stream	Master Stream 1-25/30FPS@1080P; Sub-Stream Up to 1-25/30FPS@D1		
	Master Stream	Up to 4Ch@Recording Resolution		
	Web Browser	Supported		
	CMS	Yes		
	Mobile Application	ProvisionCAM for iPhone/Android; ProvisionHD for iPad/Android Tablet		
	User Access	10 Users Online with Professional Authority Management		
Alarm	Input	16CH		
	Output	4CH		
Storage	HDD	8 SATA (6TB Each)		
	E-SATA	1		
PTZ	Connection	RS-485 / CoC		
	Supported Protocols	Pelco D, Pelco P, Samsung, Visca, CoC		
	Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus		
Network	Ethernet	1000 Mbps (RJ-45)		
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P		
Others	Dimension	W430xD450xH89mm		
	IR Controller	Yes		
	Power Supply	AC110V/220V		
	Operation Temperature	0°C ~50°C		

\*The DVR can work in Either 32Ch Half Real-Time or 16Ch Real-Time. It cannot be mixed!