

X22 ZOOM CAMERA

BZ-371CSX22
BZ-472CSX22



MODEL	BZ-371CSX22	BZ-472CSX22
Image sensor	1/3" Sony DS CCD (PAL:ICX811 AK/NTSC:ICX810 AK)	1/4 Sony CCD (PAL:ICX679AK/NTSC:ICX678AK)
DSP system	CXD 4140	
Effective Pixels	976Hx596V	
Scanning System	PAL/NTSC	
Horizontal resolution	700 TVL	
Optical zoom	22X f=3.7~81.4mm	
Sync system	Internal Sync	
Min illumination	Color: 0.3LUX, BW: 0.03LUX	
D&N	Auto/Day/Night mode	
True D&N	Yes (ICR)	No
S/N ratio	≥50db (AGC Off)	
OSD	Built In	
Focus	Auto Single/Auto Cont./Manual	
Auto gain	Auto/Manual	
Wide-D	No	
White balance	Auto	
BLC	On/Off	
AGC	High/Middle/Low	
Mirror	On/Off	
Shutter speed	1/50-1/120000 seconds	
Sense up	No	
Noise reduction	No	
Communication	RS485, Pelco D/P, B.Rate	
Power supply	DC12V/Max 210mA	DC12V/Max 180mA
Operating Temp.	0°C~+50°C	
Dimension	51mmX53mmX90mm	
Weight	540g	

Main Features:

Indoor Application
RS-485 control
Up to 22X Zoom.
Elegant and small case
OSD Menu

BZ-371CSX22

SONY 1/3" CCD
BLC/HLC/AGC
ICR
SONY EFFIO-E
2D Noise Reduction

BZ-472CSX22

SONY 1/4" CCD
BLC/HLC/AGC
SONY EFFIO-E
2D Noise Reduction

