

IR FIXED LENS DOME CAMERA

DI-390HD36

HD-SDI CAMERAS
1080P



1/3" CMOS Sensor
1080P
True Day & Night (IR Cut Removable)
0 Lux (IR On) Min. Illumination
WDR (At 15 fps)


3D Noise Reduction
DSS (Digital Slow Shutter)
BLC/HLC
Motion Detection and Privacy Masking
Digital Zoom

3.6mm Fixed Lens
15m IR Illumination
RS-485
IP66
DC 12V

Specifications

MODEL	DI-390HD36
Image Sensor	1/3" CMOS Sensor
Active Pixels	2010(H)×1092(V)
Lens	3.6mm Fixed Lens
Scanning System	Progressive Scan
Resolution	Digital: 1920x1080 (1080P 25/30FPS)
	Analog: 700TVL
Min. Illumination	0.0Lux (IR On) 24 IR LED Pieces
IR Range	15m
Video Output	Digital: HD-SDI (25/30FPS) Analog: NTSC/PAL
True D&N	ICR (IR Cut Removable)
S/N RATIO	>52dB (AGC Off)
Sharpness	Adjustable
Mirror/Flip	Yes
D-Zoom	x1 ~ x8
HLC (Eclipse)	Off/On
Brightness	Adjustable
Lens	DC/Manual
Shut Speed	Auto/Manual (1/30~1/60000)
DSS(Sense-Up)	Off/ x2~x8

AGC	Adjustable
WDR/BLC	WDR (at 15 fps) / BLC / Off
Day & Night	Auto / Day / Night / Ext
Smart IR	Yes
White BAL	ATW / Push / Indoor / Outdoor / Manual
3D-DNR	Adjustable
Privacy	Off/On (8 Areas)
Motion	Off/On (4 Areas)
Lens shading	Off/On
System	NTSC/PAL
HD Format	1080P
COMM	ID (1 ~ 255), B.Rate(2400-9600), Prot.(Pelco P/D)
OSD	Available
Power	DC 12V, 180mA (Max)
Operating Temperature	-20 C ~ 50 C, (Humidity 10% ~ 90%RH)
Dimension	92W x 69H mm
Weight	310g
IP Rating	IP66



OSD Controller



Junction Box is available