


IR VARI-FOCAL VANDAL-PROOF DOME CAMERA

DAI-340IP536



1/3" CMOS Sensor
4 Mega-Pixel
True Day & Night (IR Cut Removable)
H.265 (HEVC) Compression
0 Lux (IR On) Min. Illumination

ONVIF
Digital WDR
3D Noise Reduction
Motion Detection and Privacy Masking
3.6mm Mega-Pixel Lens

15m IR Illumination
PoE Support
1 Way Audio
CVBS
IP 66 Protection

Specifications

Camera	Video	Model	DAI-340IP536	
		Image Sensor	1/3" CMOS	
		Effective Pixels	2688x1520	
		Electronic Shutter	1/25s ~ 1/100000s	
		Day & Night	ICR	
	Audio	Audio compression	G.711A/G.711U	
		Communication	One-way Audio	
		Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
			WDR Range	Digital WDR
			Noise Reduction	3D-DNR
Image Orientation	Mirror/Flip			
Privacy Zone	Yes			
Motion Detection	Yes			
Compression	Video Compression	H.265 / H.264		
	Resolution	4MP(2560x1440), 3MP(2048x1536), 1080P, 720P, D1, CIF, 480x240		
	Multi-stream	4MP(1~30fps) / 3MP(1~30fps) / 1920x1080(1~30fps) / 1280x720(1~30fps) / D1(1~30fps) / CIF(1~30fps) / 480x240(1~30fps)		
	Bit rate	64Kbps ~ 7Mbps@H.265 / 128Kbps ~ 9Mbps@H.264		
	Encode Mode	VBR/CBR		
Image Quality	Five levels under VBR; Free adjustment under CBR			

Housing	IR Distance	15m (24 IR LED)
	Lens	3.6mm
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Water-proof	IP66
	Bracket	3-Axis Gimbal
	Dimensions	Φ116mm×91mm
	Weight(gross)	605g
	Network	RJ45 (+PoE)
	Power	DC Socket
Connectivity	Analog Video Output	CVBS (RCAX1)
	Mic Connectivity	1Ch Input
	SD Card	No
	RS485	No
	Alarm	No
	Remote Monitoring	IE Browsing, CMS Control Software
	User Access	Supports simultaneous monitoring for up to 10 users with multi-stream real time transmission
Network	Network Protocol	TCP/IP, UDP, DHCP, NTP, PPPoE, DDNS, SMTP, FTP
	ONVIF	Yes
	Ethernet	100Mbps
	PoE	Yes
	Power Supply	DC12V/~440mA / PoE/~6.7W
Others	Work Environment	-10 C ~50 C, 10%~90% Humidity

