

IR FIXED LENS VANDAL-PROOF DOME CAMERA

DAI-380IPE36 **NEW**

IP SOLUTION
1.3MP



1/3" CMOS Sensor
1.3 Mega-Pixel
True Day & Night (IR Cut Removable)
0 Lux (IR On) Min. Illumination
ONVIF

Digital WDR
3D Noise Reduction
Motion Detection and Privacy Masking
3.6mm Mega-Pixel Lens
10m IR Illumination

PoE Support
IP 66 Protection
Vandal-Proof

Specifications

Camera	Video	Model	DAI-380IPE36
		Image Sensor	1/3" CMOS
		Effective Pixels	1280×960
		Electronic Shutter	1/25s ~ 1/100000s
		Day & Night	ICR
		Min. Illumination	0lux (IR ON)
	Audio	Audio compression	No
		Communication	No
	Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
		WDR Range	Digital WDR
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
		Motion Detection	Yes
	Compression	Video Compression	H.264
Resolution		960P (1280x960), 720P (1280x720), D1 (704x567), CIF (480x240) 1280x960 (1~30fps) / 1280x720 (1~30fps)	
Multi-stream		D1 (1~30fps / CIF (1~30fps)	
Bit rate		64Kbps ~ 4Mbps	
Encode Mode		VBR/CBR	
Image Quality		Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	15m (24 IR LED)
	Lens	3.6mm
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Water-proof	IP66
	Bracket	3-Axis Gimbal
	Dimensions	Φ116mm×91mm
	Weight(gross)	605g
Connectivity	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	No
	Mic Connectivity	No
	SD Card	No
	RS485	No
Network	Alarm	No
	Remote Monitoring	IE Browsing, CMS Control Software
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Others	ONVIF	Yes
	Ethernet	100Mbps
	PoE	Yes
	Power Supply	DC12V/~440mA / PoE/~6.7W
Work Environment	-10 C ~50 C, 10%~90% Humidity	

