

IR VARI-FOCAL VANDAL-PROOF DOME CAMERA

DAI-390IPAVF



1/3" CMOS Sensor
 2 Mega-Pixel
 True Day & Night (IR Cut Removable)
 H.264+ Compression
 0 Lux (IR On) Min. Illumination

ONVIF
 Digital WDR
 3D Noise Reduction
 Motion Detection and Privacy Masking
 2.8-12mm Vari-Focal Lens

25m IR Illumination
 PoE Support
 1 Way Audio
 IP 66 Protection
 Vandal-Proof

Specifications

| | | | |
|-------------------|--|---|---|
| Camera | Video | Model | DAI-390IPAVF |
| | | Image Sensor | 1/3" CMOS |
| | | Effective Pixels | 1920×1080 |
| | | Electronic Shutter | 1/25s ~ 1/100000s |
| | | Day & Night | ICR |
| | Audio | Audio compression | G711A/U |
| | | Communication | One Way Audio |
| | Image Enhancement | Image Settings | AWB, AGC Adjustable Exposure Mode (Auto / Manual) ROI (Region of interest) Setting Sharpness, Saturation, Brightness & Contrast Adjustable |
| | | WDR Range | Digital WDR |
| | | Noise Reduction | 3D-DNR |
| Image Orientation | | Mirror/Flip/Vertical Mode | |
| Privacy Zone | | Yes | |
| Compression | Video Compression | H.264 | |
| | Resolution | 1080P (1920×1080), 720P (1280×720), VGA, QVGA | |
| | Multi-stream | 1920×1080 (1~30fps) / 1280×720 (1~30fps) / 1280×720 (1~30fps) / 640×480 (1~30fps) / 320×240 (1~30fps) | |
| | Bit rate | 128Kbps ~ 6Mbps | |
| | Encode Mode | VBR/CBR | |
| Image Quality | Five levels under VBR; Free adjustment under CBR | | |

| | | |
|--------------|---------------------|---|
| Housing | IR Distance | 25m (30 IR LED) |
| | Lens | 2.8-12mm |
| | Iris | Fixed Iris |
| | Lens Mount | Φ14 mount |
| | Water-proof | IP66 |
| | Bracket | 3-Axis Gimbal |
| | Dimensions | Φ150mm×114mm |
| Connectivity | Weight(gross) | 880g |
| | Network | RJ45 (+PoE) |
| | Power | DC Socket |
| | Analog Video Output | No |
| | Mic Connectivity | 1Ch Input |
| | SD Card | No |
| | RS485 | No |
| Network | Alarm | No |
| | Remote Monitoring | IE Browsing, CMS Control Software |
| | User Access | Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission |
| | Network Protocol | TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP |
| Others | ONVIF | Yes |
| | Ethernet | 100Mbps |
| | PoE | Yes |
| Power Supply | Power Supply | DC12V/~360mA / PoE/~6.2W |
| | Work Environment | -10 C ~50 C, 10%~90% Humidity |

