


# 30M IR FIXED LENS BULLET CAMERA

I3-340IP536



1/3" CMOS Sensor  
4 Mega-Pixel  
True Day & Night (IR Cut Removable)  
H.265 (HEVC) Compression  
0 Lux (IR On) Min. Illumination

ONVIF  
Digital WDR  
3D Noise Reduction  
Motion Detection and Privacy Masking  
3.6mm Mega-Pixel Lens

30m IR Illumination  
PoE Support  
1 Way Audio  
CVBS  
IP 66 Protection

## Specifications

Camera	Video	Model	I3-340IP536
		Image Sensor	1/3" CMOS
		Effective Pixels	2688x1520
		Electronic Shutter	1/25s ~ 1/100000s
		Day & Night	ICR
	Audio	Audio compression	G.711A/G.711U
		Communication	One-way Audio
	Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
		WDR Range	Digital WDR
		Noise Reduction	3D-DNR
Image Orientation		Mirror/Flip	
Privacy Zone		Yes	
Motion Detection		Yes	
Video Compression		H.265 / H.264	
Compression	Resolution	4MP(2688x1520), 3MP(2048x1536), 1080P, 720P, D1, CIF, 480x240	
	Multi-stream	4MP(1~30fps) / 3MP(1~30fps) / 1920x1080(1~30fps) / 1280x720(1~30fps) / D1(1~30fps) / CIF(1~30fps) / 480x240(1~30fps)	
	Bit rate	64Kbps ~ 7Mbps@H.265 / 128Kbps ~ 9Mbps@H.264	
	Encode Mode	VBR/CBR	
	Image Quality	Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	30m (42 IR LED)
	Lens	3.6mm
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Water-proof	IP66
	Bracket	3-Axis Wall Bracket
	Dimensions	Φ87mm×219mm
Connectivity	Weight(gross)	635g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	CVBS (BNCx1)
	Mic Connectivity	1Ch Input
	SD Card	No
	RS485	No
Network	Alarm	No
	Remote Monitoring	IE Browsing, CMS Control Software
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	ONVIF	Yes
Others	Ethernet	100Mbps
	PoE	Yes
Power Supply	Power Supply	DC12V/~500mA / PoE/~6.5W
	Work Environment	-10 C~50 C, 10%~90% Humidity

