

# 30M IR VARI-FOCAL BULLET CAMERA

I3-380IPVF **NEW**



1/3" CMOS Sensor  
 1.3 Mega-Pixel  
 True Day & Night (IR Cut Removable)  
 0 Lux (IR On) Min. Illumination  
 ONVIF

Digital WDR  
 3D Noise Reduction  
 Motion Detection and Privacy Masking  
 2.8-12mm Vari-Focal Lens  
 30m IR Illumination

PoE Support  
 1 Way Audio  
 IP 66 Protection

## Specifications

Camera	Video	Model	I3-380IPVF
		Image Sensor	Sony IMX138 1/3" CMOS
		Effective Pixels	1280×1024
		Electronic Shutter	1/25s ~ 1/100000s
		Day & Night	ICR
	Audio	Audio compression	G711A/U
		Communication	One Way Audio
	Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto / Manual) ROI (Region of interest) Setting Sharpness, Saturation, Brightness & Contrast Adjustable
		WDR Range	Digital WDR
		Noise Reduction	3D-DNR
Image Orientation		Mirror/Flip/Vertical Mode	
Privacy Zone		Yes	
Motion Detection		Yes	
Compression	Video Compression	H.264	
	Resolution	960P (1280×960), 720P (1280×720), VGA, QVGA 1280×960 (1~30fps) / 1280×720 (1~30fps) /	
	Multi-stream	1280x720 (1~30fps) / 640×480 (1~30fps) / 320x240 (1~30fps)	
	Bit rate	64Kbps ~ 4Mbps	
	Encode Mode	VBR/CBR	
	Image Quality	Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	30m (36 IR LED)
	Lens	2.8-12mm
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Water-proof	IP66
	Bracket	3-Axis Wall Bracket
Connectivity	Dimensions	Φ87mm×219mm
	Weight(gross)	635g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	No
	Mic Connectivity	1Ch Input
	SD Card	No
	RS485	No
Network	Alarm	No
	Remote Monitoring	IE Browsing, CMS Control Software
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	ONVIF	Yes
Others	Ethernet	100Mbps
	PoE	Yes
	Power Supply	DC12V/~500mA / PoE/~6.5W
Work Environment	-10 C~50 C, 10%~90% Humidity	

