

# 30M IR FIXED LENS BULLET CAMERA



I3-390IP04  
I3-380IP04



1/3" CMOS Sensor  
2 / 1.3 Mega-Pixel  
True Day & Night (IR Cut Removable)  
0 Lux (IR On) Min. Illumination  
ONVIF

Digital WDR  
3D Noise Reduction  
BLC/HLC  
Motion Detection and Privacy Masking  
3.6mm Mega-Pixel Lens

30m IR Illumination  
PoE Support  
1 Way Audio  
IP 66 Protection

## Specifications

Camera	Video	Model	I3-390IP04	I3-380IP04
		Image Sensor	Sony IMX122 1/3" CMOS	Sony IMX138 1/3" CMOS
Effective Pixels	1920x1080	1280x720		
Electronic Shutter	1/25s ~ 1/100000s			
Day & Night	ICR			
Min. Illumination	0lux (IR ON)			
Audio	Audio compression	G711A		
	Communication	Two Way Audio		
Image Enhancement	Image Settings	AWB, AES, AGC Adjustable Exposure Mode (Auto / Manual) BLC, HLC Adjustable Sharpness, Saturation, Brightness & Contrast Adjustable		
	WDR Range	Digital WDR		
	Noise Reduction	3D-DNR		
	Image Orientation	Mirror/Flip		
	Privacy Zone	Yes		
	Motion Detection	Yes		
	Video Compression	H.264		
Compression	Resolution	1080P (1920x1080)*, 960P (1280x960)*, 720P (1280x720), VGA, QVGA		
	Multi-stream	1920x1080 (1~30fps)* / 1280x960 (1~30fps) / 1280x720 (1~30fps) / 1280x720 (1~30fps) / 640x480 (1~30fps) / 320x240 (1~30fps)		
	Bit rate	64Kbps ~ 8Mbps	64Kbps ~ 4Mbps	
	Encode Mode	VBR/CBR		
	Image Quality	Five levels under VBR; Free adjustment under CBR		

Housing	IR Distance	30m (42 IR LED)
	Lens	3.6mm
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Water-proof	IP66
	Bracket	3-Axis Wall Bracket
	Dimensions	Φ87mm×219mm
Weight(gross)	635g	
Connectivity	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	CVBS (BNCx1)
	Mic Connectivity	1Ch Input
	SD Card	No
	RS485	No
	Alarm	No
Network	Remote Monitoring	IE Browsing, CMS 2.0 Control Software
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	ONVIF	Yes
	Ethernet	100Mbps
PoE	Yes	
Others	Power Supply	DC12V/PoE
	Work Environment	-10 C~50 C, 10%~90% Humidity

\*I3-390IP04 Model Only

