

40M IR VARI-FOCAL BULLET CAMERA

I4-310IPEHVF



1/3" CMOS Sensor
 3 Mega-Pixel
 True Day & Night (IR Cut Removable)
 0 Lux (IR On) Min. Illumination
 ONVIF
 Digital WDR

3D Noise Reduction
 Motion Detection and Privacy Masking
 2.8-12mm Vari-Focal Lens
 40m IR Illumination
 PoE Support
 Local Storage

IP 66 Protection
 Vandal-Proof

Specifications

Camera	Video	Model	I4-310IPEHVF	
		Image Sensor	1/3" CMOS	
		Effective Pixels	2048×1536	
		Electronic Shutter	1/25s ~ 1/100000s	
		Day & Night	ICR	
	Audio	Audio compression	NO	
		Communication	NO	
	Image Enhancement	Image Settings	AWB(Adjustable), AGC, AES(Auto) Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable	
		WDR Range	Digital WDR(Real WDR optional)	
		Noise Reduction	2D/3D-DNR	
Image Orientation		Mirror/Flip		
Privacy Zone		Yes		
Compression	Video Compression	H.264		
	Resolution	3MP(2048×1536), 1080P(1920×1080), 720P(1280×720), D1, CIF, 480x240		
	Multi-stream	3MP(1~15fps) / 1920x1080(1~30fps) / 1280x720(1~30fps) / D1(1~30fps) / CIF(1~30fps) / 480x240(1~30fps)		
	Bit rate	64Kbps ~ 8Mbps		
	Encode Mode	VBR/CBR		
	Image Quality	Five levels under VBR; Free adjustment under CBR		

Housing	IR Distance	40m
	Lens	2.8-12mm
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Water-proof	IP66
	Bracket	3-Axis Wall Bracket
	Dimensions	Φ109mm×284mm
Connectivity	Weight(gross)	1091g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	No
	Mic Connectivity	No
	SD Card	Support TF (64GB Max)
	RS485	No
Network	Alarm	No
	Remote Monitoring	IE Browsing, CMS 3 Control Software
	User Access	Supports simultaneous monitoring for up to 10 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, PPPoE, DDNS, SMTP, FTP
	ONVIF	Yes
Others	Ethernet	100Mbps
	PoE	Yes
	Power Supply	DC12V/POE
Work Environment	-10 C~50 C, 10%~90% Humidity	

