


32CH NVR (16CH PoE)

NVR3-32800-16P(2U)

3MP



Plug & View



MODEL		NVR3-32800-16P (2U)
Video	Input	32CH Over Network
	Output	HDMI, VGA (800x600, 1024x768, 1280x1024)
	Decoding	H.264
Audio	Input	1CH + Depends on Camera Stream
	Output	1CH
	Two Way Audio	Yes
Bandwidth	Incoming	200Mbps
	Outgoing	24Mbps
Recording	Real-Time Recording	32CH 3MP Real-Time
	3MP	960FPS (NTSC)/800FPS (PAL)
	2MP (1080P)	960FPS (NTSC)/800FPS (PAL)
	1.3MP (960P)	960FPS (NTSC)/800FPS (PAL)
	1MP (720P)	960FPS (NTSC)/800FPS (PAL)
	960H	No
	D1	960FPS (NTSC)/800FPS (PAL)
	CIF	No
Recording Modes	Schedule, Manual, Motion, Sensor	
Playback	Playback Channel	4CH
	Search Mode	Time, Event, File Management
Backup	USB	1 USB 2.0 + 1 USB 3.0 Ports
	DVD Burner	Optional
	Backup Format	AVI/DAT
Remote Application	Master Stream	Up to 4CH@Recording Resolution
	Sub-Stream	1-25/30FPS@CIF
	Browser	IE, Chrome, Safari, Firefox (Mac OS, Windows XP/Vista/7/8)
	CMS	Yes
	Mobile Application	ProvisionCAM for iPhone/Android Phone Provision HD for iPad/Android Tablet
User Access	20 Users Online with Professional Authority Management	
Alarm	Input	16
	Output	4
Storage	HDD	8 SATA (4TB)
	E-SATA	1
PTZ	Connection	Yes via Network
	Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
	RS-485	Yes
Network	Ethernet	1000 Mbps (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P
	ONVIF	Yes
PoE	Ports	Yes (16CH)
	Interface	10/100Mbps
	Standard	IEEE802.3AF
	Total Power	150W (Average 9W Per Channel)
	Max. Power Consumption (Per Channel)	15W
Others	Power Supply	AC110V/220V
	Power Consumption (No HDD)	30W
	Dimension	W430 x D450 x H89
	Operation Temperature	0°C ~50°C