

32CH NVR

NVR5-32800(1U)



5MP



MODEL		NVR5-32800 (1U)
Video	Input	32CH over Network
	Output	HDMI (4K, 1080P), VGA (1280x1024)
	Decoding	H.265 / H.264
Audio	Input	1CH + Depends on Camera Stream
	Output	1CH + Depends on Camera Stream
	Two Way Audio	Yes
Bandwidth	Incoming	256Mbps
	Outgoing	256Mbps
Recording	Real-Time Recording	32CH 5MP Real-Time
	5MP	960FPS (NTSC)/800FPS (PAL)
	4MP	960FPS (NTSC)/800FPS (PAL)
	3MP	960FPS (NTSC)/800FPS (PAL)
	2MP (1080P)	960FPS (NTSC)/800FPS (PAL)
	1.3MP (960P)	960FPS (NTSC)/800FPS (PAL)
	1MP (720P)	960FPS (NTSC)/800FPS (PAL)
	960H	No
	D1	960FPS (NTSC)/800FPS (PAL)
Playback	CIF	No
	Recording Modes	Schedule, Manual, Motion, Sensor
	Playback Channels	16CH
	Search Mode	Time-Slice, Time, Event, File Management
Backup	USB	1 USB 2.0 Port + 1 USB 3.0 Port
	DVD Burner	No
	Backup Format	AVI/DAT
Remote Application	Master Stream	Up to 32CH@Recording Resolution
	Sub-Stream	Depends on IPC
	Browser	IE, Safari, Firefox (Mac OS, Windows Vista/7/8/10)
	CMS	Yes
	Mobile Application	Provision CAM2 for iPhone/Android Phones/Tablets
Alarm	User Access	10 Users Online with Professional Authority Management
	Input	Depends on Camera
Storage	Output	Depends on Camera
	HDD	2 SATA (6TB Each)
PTZ	E-SATA	No
	Connection	Via Network
	Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
Network	RS-485	No
	Ethernet	1000 Mbps (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P
PoE	ONVIF	Yes
	Ports	No
	Interface	No
	Standard	No
	Total Power	No
Others	Max. Power Output (Per Ch.)	No
	Power Supply	DC12V/4A
	Power Consumption (No HDD)	15W
	Dimension	W375xD275xH45mm
	Operation Temperature	0°C ~50°C